

TIB KAT[®] 423

TIB KAT 423 is a liquid catalyst blend based on a dioctyltin oxide formulation.

TIB KAT 423 can be applied for the curing of silicones and silane terminated polymer systems, especially for

- curing 1K MS Silyl systems
- curing of alkoxy based based RTV-silicones.

Product data	
Formula	DOT-silane blend
State of aggregation	liquid
Solubility	miscible with alcohols, hydrolysis in water

Specification	
Tin content	> 21.5 wt.-%
Colour (Gardner)	< 5

Storage

TIB KAT 423 can be stored at least 6 months from date of delivery if kept closed in the original packaging at ambient temperature and in a dry place protected against temperature raise and excessive of humidity.

TIB KAT 423 is sensitive to moisture and therefore contact has to be minimized. At higher humidity weather conditions hydrolyses can be occur and leads to decreasing flash points. Intertisation of once opened drums with nitrogen is recommended.

Packaging

200 kg plastic drum,
other packaging size upon request.

Special advice for security

Information concerning

- classification and labelling according to the regulations governing transport and hazardous chemicals
- protective measures for storage and handling
- safety measures in case of accident and fire
- toxicity and ecological effects

is given in our material safety data sheet.

Customs Tariff No.: 3815 90 90

Issue / Mar 15

TIB Chemicals AG | Mülheimer Strasse 16 -22| D-68219 Mannheim| P.O. Box 81 02 20| D-68202 Mannheim
Phone +49 (0) 621 8901- 811| Fax +49 (0) 621 8901- 475| info.@tib-chemicals.com| www.tib-chemicals.com

This information is given to the best of our knowledge but without obligation. We are not liable for any wrong advice or any advice we may have failed to give. This data sheet becomes invalid as soon as a new edition has been published. Please contact us for latest.

