

METOLAT[®] P 13

TECHNICAL INFORMATION

Shrinkage reduction agent

Composition:	Blend of glycols with an inorganic carrier	
Appearance:	powder	
Colour:	white	
Typical Properties:	Ash:	approx. 50 %
	Consistency:	free flowing powder
	Apparent density:	approx. 460 g/l
	Solubility in water:	active ingredients soluble in water

This information is intended as a guideline only and should not be used to issue specifications. Slight deviations do not affect application and capability of the product. For specifications please consult the Certificate of Analysis.

Properties/applications: METOLAT P 13 is recommended for the use in dry mixtures which are to be blended or diluted with water prior to application. METOLAT P 13 reduces the shrinkage in cementitious systems.

Main applications:
- Cementitious mortars
- Leveling compounds
- Screeds (cement based)

Recommended levels/use: Normal dosage ranges from 0.5 to 5.0 % for anti-shrink properties. The optimum concentration will vary depending on the system and should be tested.

Storage/handling: METOLAT P 13 should be stored dry between 15 and 25 °C. The minimum shelf life in closed containers is 15 months from the date of manufacture.

Packaging: Pallet with 30 bags, each 20 kg (600 kg)

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.

EN

Revision: May 2017

MÜNZING CHEMIE GmbH
Münzingstrasse 2
74232 Abstatt

Tel.: +49(0)7131/987-0
Fax: +49(0)7131/987-125
sales.pca@munzing.com
www.munzing.com

